

**WHAT IS CLAIMED IS:**

1. In a cellular mobile radio communications system supporting communications over a radio interface between a radio network and mobile terminals, a method comprising:

5 determining a load condition of a cell, without having to measure a radio parameter, based on issued transmit power control commands, and  
regulating a traffic condition in the cell based on the determined load situation.

10 2. The method in claim 1, wherein the traffic condition relates to a load condition in the cell.

3. The method in claim 1, wherein the traffic condition relates to a capacity in the cell.

15 4. The method in claim 1, wherein the traffic condition is an interference level in the cell, the method further comprising:

controlling the interference level using the determined value of the load condition.

5. The method in claim 1, wherein the traffic condition is transmit power level, the method further comprising:

20 controlling a transmit power of a base station or a channel in the cell using the determined value of the radio condition.

6. The method in claim 1, wherein the traffic condition is transmit power, the method further comprising:

controlling the transmit power of a mobile station using the determined load condition.

7. The method in claim 1, wherein the load condition is related to a power level.

8. The method in claim 7, wherein the power level is the total power level detected at a base station in the cell.

5 9. The method in claim 1, wherein the determining of the load condition of a cell without having to measure a radio parameter includes monitoring a number of increase transmit power commands issued in a cell over a time period relative to a total number of transmit power commands issued in the cell for that time period.

10. The method in claim 9, further comprising:  
10 if the number of increase transmit power commands relative to the total number of transmit power commands exceeds a threshold, taking action to reduce the amount of traffic in the cell.

11. The method in claim 10, wherein the action is reducing a signal level in the cell.

15 12. The method in claim 1, wherein the determining of the load condition of a cell without having to measure a radio parameter includes monitoring a first number of increase transmit power commands issued in a cell over a time period relative to a second number of decrease transmit power commands issued in the cell for that time period.

20 13. The method in claim 12, further comprising:  
if a difference between the number of increase transmit power commands and the number of decrease transmit power commands exceeds a threshold, taking action to reduce the number of increase transmit power commands in the cell.

25 14. The method in claim 13, wherein the action is reducing a signal level in the cell.

15. The method in claim 1, further comprising:  
 measuring a value associated with the load condition, and  
 using the measured value along with the determined value of the load  
 condition to regulate the traffic condition in the mobile radio communications  
 5 system.

16. The method in claim 15, wherein the measured value is a received  
 power or interference level in the cell.

17. The method in claim 1, further comprising:  
 weighting each issued transmit power control command based on a  
 10 predetermined factor, and  
 determining the load situation based on the weighted commands.

18. The method in claim 17, wherein the predetermined factor is a  
 bit rate associated with the issued transmit power control command.

19. The method in claim 17, wherein the predetermined factor is the  
 15 activity factor of a connection associated with the issued transmit  
 power control command.

20. In a mobile radio communications system supporting communications  
 over a radio interface between a radio network and mobile terminals, a method  
 comprising:

20 determining a first number of transmit power increase commands from the  
 radio network to mobile terminals in a cell in a time period;

determining a second number of transmit power commands from the radio  
 network to mobile terminals in a cell in the time period;

determining a third number associated with the first and second numbers for  
 25 the time period;

comparing the third number to a first threshold; and

if the third number exceeds the first threshold, indicating an undesirable condition in the cell.

21. The method in claim 20, wherein the second number is a total number of transmit power commands in the time period, and the third number is a percentage of the first number to the second number.

22. The method in claim 20, wherein the second number is a number of decrease transmit power commands in the time period, and the third number is a difference between the first number and the second number.

23. The method in claim 21, wherein the first number is determined by counting transmit power increase commands and the second number is determined by counting transmit power decrease commands.

24. The method in claim 20, further comprising:  
determining an average of the third number over a predetermined time interval,  
wherein the averaged third number is compared to the first threshold.

25. The method in claim 20, further comprising:  
determining a rate of change of the third number;  
determining if the rate of change of the third number exceeds a second threshold; and  
if it does, decreasing the first threshold.

26. The method in claim 20, further comprising:  
measuring a signal level in the cell;  
comparing the measured signal level in the cell to a signal level threshold; and

if the measured level in the cell exceeds the signal level threshold and if the third number exceeds the first threshold, indicating an undesirable condition in the cell.

27. The method in claim 20, wherein the undesirable condition is an  
5 overload condition.

28. The method in claim 20, wherein the undesirable condition is too high  
of an interference or power level in the cell.

29. The method in claim 20, further comprising:  
regulating a traffic condition of the cell if the undesirable condition is signaled.

30. The method in claim 20, further comprising:  
performing congestion control in the cell if the undesirable condition is  
10 signaled.

31. The method in claim 20, further comprising:  
performing admission control in the cell based on a comparison of the third  
15 number and the first threshold.

32. The method in claim 20, wherein the increase transmit power  
commands increment a counter and the decrease transmit power commands  
decrement the counter.

33. The method in claim 19, wherein the first and second numbers are  
20 based on weighted transmit power commands.

34. In a mobile radio communications system supporting communications  
over a radio interface between a radio network and mobile terminals, a radio  
network node, comprising:

a counter for counting a first number of transmit power increase commands from the radio network to mobile terminals in a cell in a time period and a second number of transmit power commands from the radio network to mobile terminals in a cell in the time period;

5 a first comparator for comparing a third number associated with the first and second numbers for the time period with a first threshold; and

a controller for detecting an undesirable condition in the cell if the third number exceeds the first threshold.

35. The radio network node in claim 34, wherein the second number is a  
10 total number of transmit power commands in the time period, and the third number is a percentage of the first number to the second number.

36. The radio network node in claim 34, wherein the second number is a  
number of decrease transmit power commands in the time period, and the third  
number is a difference between the first number and the second number, and  
15 wherein the counter is incremented with each increase transmit power command and decremented for each decrease transmit power command.

37. The radio network node in claim 34, wherein the first number is  
determined by counting transmit power increase commands and the second number  
is determined by counting transmit power decrease commands.

20 38. The radio network node in claim 34, further comprising:  
an averager for determining an average of the third number over a  
predetermined time interval,

wherein the first comparator compares the third number to the first  
threshold.

25 39. The radio network node in claim 34, further comprising:  
a rate of change detector for determining a rate of change of the third number;

a second comparator for determining if the rate of change of the third number exceeds a second threshold,

wherein if the rate of change of the third number exceeds a second threshold, the controller decreases the first threshold.

5        40.    The radio network node in claim 34, further comprising:  
a sensor used for measuring a signal level in the cell, and  
a second comparator for comparing the measured signal level in the cell to a  
signal level threshold,

10        wherein if the measured signal level in the cell exceeds the signal level  
threshold and if the third number exceeds the first threshold, the controller detects  
the undesirable condition in the cell.

41.    The radio network node in claim 34, wherein the undesirable condition  
is an overload condition.

15        42.    The radio network node in claim 34, wherein the undesirable condition  
is too high of an interference or power level in the cell.

43.    The radio network node in claim 34, wherein the controller regulates a  
traffic condition of the cell if the undesirable condition is detected.

44.    The radio network node in claim 34, wherein the first and second  
numbers are based on weighted transmit power commands.

20        45.    In a cellular mobile radio communications system supporting  
communications over a radio interface between a radio network and mobile  
terminals, apparatus comprising:

25        electronic circuitry configured to determine a load condition of a cell, without  
having to measure the load condition, based on issued transmit power control  
commands, and

a controller configured to regulate a traffic condition in the cell based on the determined load condition.

46. The apparatus in claim 45, wherein the electronic circuitry includes a counter.

5 47. The apparatus in claim 46, wherein the counter is configured to increment with each increase transmit power command and to decrement with each decrease transmit power command.

48. The apparatus in claim 47, further comprising:  
means for averaging the counter output.

10 49. The apparatus in claim 48, further comprising:  
means for determining a derivative of the counter output.

50. The apparatus in claim 48, further comprising:  
means for measuring a power level in the cell,  
wherein the controller is configured to regulate a traffic condition in the cell  
15 based on the determined load condition and the measured power level in the cell.

51. The apparatus in claim 45, further comprising:  
means for weighting the issued transmit power control commands based on a  
predetermined factor,

wherein the electronic circuitry is configured to determine the load condition  
20 based on the weighted commands.

52. The apparatus in claim 51, wherein the predetermined factor is a bit  
rate associated with the issued transmit power control command.